



# EC safety data sheet

Trade name: MARAPROP PP

Status: 01.04.01

Product no.: 3356

Version : 1 / GB

page:

1(7)

## 1.) Identification of the substance/preparation and company

### Product details

#### Trade name

MARAPROP PP

### Identification of the manufacturer / supplier

#### Address

Marabuwerke GmbH & Co. KG

Asperger Straße 4

D-71732 Tamm, Germany

Telephone no. +49 7141/691-0

Fax no. +49 7141/691-235

#### Information provided by / telephone

product safety/+49 7141/691-116 or 232

#### Emergency telephone number

product safety/+49 7141/691-116 or 232

## 2.) Composition / information on ingredients

### Chemical characterization

Screen printing ink based on acrylic resins and on solvents

### Hazardous ingredients

#### **SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.**

CAS no. 64742-95-6

Concentration >= 10 < 25 %-b.w.

Hazard symbols N, Xn R phrases 51/53, 66, 67, 65, 10, 37

#### **2-METHOXY-1-METHYLETHYL ACETATE**

CAS no. 108-65-6

Concentration >= 5 < 15 %-b.w.

Hazard symbols Xi R phrases 10, 36

#### **SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM.**

CAS no. 64742-94-5

Concentration >= 5 < 15 %-b.w.

Hazard symbols N, Xn R phrases 65, 51/53

#### **XYLENE**

CAS no. 1330-20-7

Concentration >= 1 < 10 %-b.w.

Hazard symbols Xn R phrases 10, 20/21, 38

#### **ETHYLBENZENE**

CAS no. 100-41-4

Concentration >= 1 < 5 %-b.w.

Hazard symbols Xn, F R phrases 11, 20

## 3.) Hazards possibilities

### Hazard symbols

Xi Irritant

### R phrases

10 Flammable.  
37 Irritating to respiratory system.



## EC safety data sheet

Trade name: MARAPROP PP

Status: 01.04.01

Product no.: 3356

Version : 1 / GB

page:

2(7)

### Particular information pertaining specific risk for human / environment

The product is water polluting.

## 4.) First aid measures

### General information

Immediately remove all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. Unconsciousness: lateral position - call a physician.

### After inhalation

Take the casualty into the fresh air and keep warm. Irregular breathing/no breathing: artificial respiration. Call a physician.

### After skin contact

Wash away with soap and water and rinse. Do NOT use solvents or thinners!

### After eye contact

Flush with plenty of water (10 - 15 min.). Call a physician.

### After ingestion

Call a doctor. Keep at rest. Do not induce vomiting.

## 5.) Firefighting measures

### Suitable extinguishing media

Carbon dioxide, foam, sand, dry extinguishing agent.

### Extinguishing media that must not be used for safety reasons

Waterjet should not be used because water is not mixable with a lot of organic solvents and such solvents will spread on the water surface.

### Special exposure hazards arising from the substance or preparation itself, its combustion products or from resulting gases

In case of fire, dangerous smoke gases such as carbon dioxide, carbon monoxide, soot, nitrogen oxides, metal oxides and halogenated hydrogens can be produced. Therefore, take suitable precautionary measures for fire fighting. Residues remaining after a fire have to be disposed of appropriately.

### Special protective equipment for firefighting

Breathing apparatus with an independent source of air may be required.

### Other information (chapter 5.)

Cool endangered containers with water in case of fire.

## 6.) Accidental release measures

### Personal precautions

Keep away from sources of ignition. Provide for good ventilation. Do not breathe vapours. Refer to protective measures listed in sections 7 and 8.

### Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

### Methods for cleaning up/taking up

Remove by liquid absorbing material (e.g. kieselguhr) and process according to waste regulations. Clean preferably with a detergent; avoid use of solvents.



## EC safety data sheet

Trade name: MARAPROP PP

Status: 01.04.01

Product no.: 3356

Version : 1 / GB

page:

3(7)

## 7.) Handling and storage

### Handling

#### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limit. Do not leave containers open. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. When using do not eat, drink or smoke. Comply with the health and safety at work laws.

#### Advice on protection against fire and explosion

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing. No sparking tools should be used.

#### Classification of fires

B (Combustible liquid substances)

#### Ignition group

T3

### Storage

#### Requirements for storage rooms and vessels

Recommended storage temperature: 15-20°C. Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

#### Hints on storage assembly

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

#### Further information on storage conditions

Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep away from sources of ignition. Keep containers dry and cool.

## 8.) Exposure controls / personal protection

#### Additional hints on technical system design.

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

#### Ingredients with occupational exposure limits to be monitored

##### XYLENE

CAS no. 1330-20-7  
EINECS no. 215-535-7

##### OES/EH40

|                                      |     |                   |     |                   |
|--------------------------------------|-----|-------------------|-----|-------------------|
| LTEL                                 | 100 | ml/m <sup>3</sup> | 441 | mg/m <sup>3</sup> |
| STEL                                 | 150 | ml/m <sup>3</sup> | 662 | mg/m <sup>3</sup> |
| Skin resorption /<br>sensibilisation | Sk  |                   |     |                   |

##### ETHYLBENZENE

CAS no. 100-41-4  
EINECS no. 202-849-4

##### OES/EH40

|      |     |                   |     |                   |
|------|-----|-------------------|-----|-------------------|
| LTEL | 100 | ml/m <sup>3</sup> | 441 | mg/m <sup>3</sup> |
| STEL | 125 | ml/m <sup>3</sup> | 552 | mg/m <sup>3</sup> |



## EC safety data sheet

Trade name: MARAPROP PP

Status: 01.04.01

Product no.: 3356

Version : 1 / GB

page:

4(7)

### MESITYLENE

CAS no. 108-67-8  
EINECS no. 203-604-4

OES/EH40

LTEL 25 ml/m<sup>3</sup> 125 mg/m<sup>3</sup>

### 1,2,4-TRIMETHYLBENZENE

CAS no. 95-63-6  
EINECS no. 202-436-9

OES/EH40

LTEL 25 ml/m<sup>3</sup> 125 mg/m<sup>3</sup>

### AROMATICS

OES/EH40

LTEL 500 mg/m<sup>3</sup>

## Personal protective equipment

### Respiratory protection

Breathing protection equipment required in inadequately ventilated places and during spraying.

Respiratory filter (gas) : A

Respiratory filter (part): P2

### Hand protection

Use protective gloves.

### Eye protection

Use safety glasses.

### Skin protection

Personal should wear antistatic clothing made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact. Use re-greasing skin cream.

### General protective and hygiene measures

The usual precautionary measures for the handling of chemicals have to be observed.

## 9.) Physical and chemical properties

### Appearance

Form pasty  
Colour see trade name  
Odour characteristic

### Safety data

#### Changes in physical state

Type Boiling point (initial)  
Value 140 °C

#### Flash point

Value 45 °C  
Method ASTM D 6450 (CCCFP)

#### Ignition temperature

Value 272 °C

#### Explosion limits

Upper explosion limit 10,0 % vol  
Lower explosion limit 0,6 % vol



## EC safety data sheet

Trade name: MARAPROP PP

Status: 01.04.01

Product no.: 3356

Version : 1 / GB

page:

5(7)

### Vapour pressure

|                       |    |    |     |
|-----------------------|----|----|-----|
| Value                 | 4  |    | hPa |
| Reference temperature | 20 | °C |     |

### Density

|                       |     |       |                   |
|-----------------------|-----|-------|-------------------|
| Value                 | 0,9 | - 1,5 | g/cm <sup>3</sup> |
| Reference temperature | 20  | °C    |                   |

### Viscosity

|                       |              |    |     |
|-----------------------|--------------|----|-----|
| Type                  | Flow time    |    |     |
| Value                 | > 150        |    | sec |
| Method                | DIN-cup 4 mm |    |     |
| Reference temperature | 20           | °C |     |

### Solubility in water

Remarks parts of solvents

### Other information (chapter 9.)

The physical specifications are approximate values and refer to the used safety relevant component(s).

## 10.) Stability and reactivity

### Conditions to avoid

Stable under recommended storage and handling conditions (See section 7).

### Materials to avoid

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### Hazardous decomposition products

When exposed to high temperatures, dangerous decomposition products such as carbon dioxide, carbon monoxide, soot, nitrogen oxides, metal oxides and halogenated hydrocarbons can be produced.

## 11.) Toxicological information

### Experience in practice

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause symptoms like described above by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Splashes in the eyes may cause pronounced burning pains. If swallowed, stomach complaints and irritation of the digestive organs may result.

### Other information (chapter 11.)

There are no data available on the preparation itself.

The product was classified in toxicological terms on the basis of the results of the calculation procedure outlined within General Directive on Preparations (88/379/EEC).

## 12.) Ecological information

### General information / ecology

There are no data available on the preparation itself.  
Do not empty into waters or drains



## EC safety data sheet

Trade name: MARAPROP PP

Status: 01.04.01

Product no.: 3356

Version : 1 / GB

page:

6(7)

### 13.) Disposal considerations

#### Product

Dispose of or incinerate in accordance with corresponding regulations.

Code of waste pursuant to European Council Directive on waste: 080302 (Wastes from the manufacture, formulation, supply and use (MFSU) of coatings (paints, varnishes and vitreous enamels), adhesive, sealants and printing inks - wastes from MFSU of printing inks - waste ink free of halogenated solvents).

#### Uncleaned packaging

Dispose of only completely emptied containers!

Code of waste pursuant on European Council Directive on waste: 150104 (Packaging; absorbents, wiping cloths, filter materials and protective clothing not otherwise specified - packaging - metallic).

### 14.) Transport information

#### Land transport ADR/RID

|         |   |
|---------|---|
| Class   | 3* 31 c   |
| Remarks | Containers with a capacity <= 450 ltrs are subject only to the regulations of Rn. 2314 (remarks under E of Rn. 2301). |

#### Marine transport IMDG/GGVSee

|                      |       |
|----------------------|-------|
| Class                | 3.3   |
| Packaging group      | III   |
| UN number            | 1263  |
| Proper shipping name | Paint |
| EmS                  | 3-05  |
| MFAG                 | 310   |
| MARPOL               | MP    |
| Label                | 3     |

#### Air transport ICAO/IATA

|                      |       |
|----------------------|-------|
| Class                | 3     |
| Packaging group      | III   |
| UN number            | 1263  |
| Proper shipping name | Paint |
| Label                | 3     |

### 15.) Regulatory information

#### Hazard symbols

Xi      Irritant

#### R phrases

|    |                                   |
|----|-----------------------------------|
| 10 | Flammable.                        |
| 37 | Irritating to respiratory system. |

#### S phrases

|       |   |
|-------|---|
| 20/21 | When using do not eat, drink or smoke.  |
| 24    | Avoid contact with skin.  |
| 26    | In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. |
| 29    | Do not empty into drains.   |
| 51    | Use only in well-ventilated areas.  |



## EC safety data sheet

Trade name: MARAPROP PP

Status: 01.04.01

Product no.: 3356

Version : 1 / GB

page:

7(7)

### 16.) Other information

#### **Other information**

According to their chemical structure, the applied raw materials do not contain any antimony, arsenic, soluble barium, lead, cadmium, chromium, mercury and selenium.

#### **Department issuing safety data sheet**

Laboratory/product safety.

#### **Contact person**

Dipl.-Chem. G. Heller or Dipl.-Ing. U. Voetter.

The instructions are based on today's information and knowledge. The safety data sheet describes products in relation to safety requirements. These instructions do not assure application technological properties of the product.

Date of printing : 02.02.2003