



EC safety data sheet

Trade name: SCREEN OPENER SPRAY

Status: 01.04.01

Product no.: 3514xx002

Version : 1 / GB

page:

1(6)

1.) Identification of the substance/preparation and company

Product details

Trade name

SCREEN OPENER SPRAY

Identification of the manufacturer / supplier

Address

Marabuwerke GmbH & Co. KG

Asperger Straße 4

D-71732 Tamm, Germany

Telephone no. +49 7141/691-0

Fax no. +49 7141/691-235

Information provided by / telephone

product safety/+49 7141/691-116 or 232

Emergency telephone number

product safety/+49 7141/691-116 or 232

2.) Composition / information on ingredients

Chemical characterization

Reactive agent solution: Solvent mixture of aromatic hydrocarbons (C9-C10), esters and ketones

Propellant: Propane-butane

Hazardous ingredients

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

CAS no. 64742-95-6

Concentration >= 30 < 35 %-b.w.

Hazard symbols N, Xn R phrases 51/53, 66, 67, 65, 10, 37

CYCLOHEXANONE

CAS no. 108-94-1

Concentration >= 20 < 25 %-b.w.

Hazard symbols Xn R phrases 10, 20

2-METHOXY-1-METHYLETHYL ACETATE

CAS no. 108-65-6

Concentration >= 15 < 20 %-b.w.

Hazard symbols Xi R phrases 10, 36

BUTANE

CAS no. 106-97-8

Concentration >= 15 < 20 %-b.w.

Hazard symbols F+ R phrases 12

3.) Hazards possibilities

Hazard symbols

F+ Extremely flammable Xi Irritant

R phrases

37 Irritating to respiratory system.

Particular information pertaining specific risk for human / environment

The product is water polluting.



EC safety data sheet

Trade name: SCREEN OPENER SPRAY

Status: 01.04.01

Product no.: 3514xx002

Version : 1 / GB

page:

2(6)

4.) First aid measures

General information

Immediately remove all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. Unconsciousness: lateral position - call a physician.

After inhalation

Take the casualty into the fresh air and keep warm. Irregular breathing/no breathing: artificial respiration. Call a physician.

After skin contact

Wash away with soap and water and rinse. Do NOT use solvents or thinners!

After eye contact

Flush with plenty of water (10 - 15 min.). Call a physician.

After ingestion

Call a doctor. Keep at rest. Do not induce vomiting.

5.) Firefighting measures

Suitable extinguishing media

Carbon dioxide, foam, sand, dry extinguishing agent.

Extinguishing media that must not be used for safety reasons

Waterjet should not be used because water is not mixable with a lot of organic solvents and such solvents will spread on the water surface.

Special exposure hazards arising from the substance or preparation itself, its combustion products or from resulting gases

In case of fire, dangerous smoke gases such as carbon dioxide, carbon monoxide and soot can be produced. Therefore, take suitable precautionary measures for fire fighting. Residues remaining after a fire have to be disposed of appropriately.

Special protective equipment for firefighting

Breathing apparatus with an independent source of air may be required.

Other information (chapter 5.)

Cool endangered containers with water in case of fire.

6.) Accidental release measures

Personal precautions

Keep away from sources of ignition. Provide for good ventilation. Do not breathe vapours. Refer to protective measures listed in sections 7 and 8.

Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

Methods for cleaning up/taking up

Remove by liquid absorbing material (e.g. kieselguhr) and process according to waste regulations. Clean preferably with a detergent; avoid use of solvents.

7.) Handling and storage

Handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limit. Do not leave containers open.



EC safety data sheet

Trade name: SCREEN OPENER SPRAY

Status: 01.04.01

Product no.: 3514xx002

Version : 1 / GB

page:

3(6)

The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. When using do not eat, drink or smoke. Comply with the health and safety at work laws.

Advice on protection against fire and explosion

Keep away from ignition sources - No smoking. Do not store alongside highly flammable materials. Operators should wear antistatic footwear and clothing. No sparking tools should be used.

Classification of fires

B (Combustible liquid substances)

Ignition group

T3

Storage

Requirements for storage rooms and vessels

Gases in pressurized containers should not be allowed to be heated over 50°C by sunshine or other heat sources. Regard special prescriptions for storage of pressurized containers.

Hints on storage assembly

Do not store alongside highly flammable materials.

Further information on storage conditions

Keep away from sources of ignition. Keep containers dry and cool.

8.) Exposure controls / personal protection

Additional hints on technical system design.

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If this is insufficient to keep the concentration of the propellant and of the vapours of the solvents contained in this product be low the OEL, suitable respiratory protection must be worn.

Ingredients with occupational exposure limits to be monitored

BUTANE

CAS no. 106-97-8
EINECS no. 203-448-7

OES/EH40

LTEL 600 ml/m³ 1450 mg/m³

STEL 700 ml/m³ 1810 mg/m³

MESITYLENE

CAS no. 108-67-8
EINECS no. 203-604-4

OES/EH40

LTEL 25 ml/m³ 125 mg/m³

CYCLOHEXANONE

CAS no. 108-94-1
EINECS no. 203-631-1

OES/EH40

LTEL 25 ml/m³ 102 mg/m³

STEL 100 ml/m³ 408 mg/m³

1,2,4-TRIMETHYLBENZENE

CAS no. 95-63-6
EINECS no. 202-436-9

OES/EH40

LTEL 25 ml/m³ 125 mg/m³



EC safety data sheet

Trade name: SCREEN OPENER SPRAY

Status: 01.04.01

Product no.: 3514xx002

Version : 1 / GB

page:

4(6)

AROMATICS

OES/EH40

LTEL 500 mg/m³

Personal protective equipment

Respiratory protection

Breathing protection equipment required in inadequately ventilated workplaces.

Respiratory filter (gas) : A

Respiratory filter (part): P2

Hand protection

Use protective gloves.

Eye protection

Use safety glasses.

Skin protection

Personal should wear antistatic clothing made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact. Use re-greasing skin cream.

General protective and hygiene measures

The usual precautionary measures for the handling of chemicals have to be observed.

9.) Physical and chemical properties

Appearance

Form Solution: liquid
Colour clear, colourless
Odour characteristic

Safety data

Changes in physical state

Type Boiling point (initial)
Value 140 °C

Flash point

Value 43 °C
Method ASTM D 6450 (CCCFP)

Ignition temperature

Value 272 °C

Explosion limits

Upper explosion limit 10,0 % vol
Lower explosion limit 0,7 % vol

Vapour pressure

Value 4 hPa
Reference temperature 20 °C

Density

Value 0,92 g/cm³
Reference temperature 20 °C

Viscosity

Type Flow time
Value < 12 sec
Method DIN-cup 4 mm
Reference temperature 20 °C



EC safety data sheet

Trade name: SCREEN OPENER SPRAY

Status: 01.04.01

Product no.: 3514xx002

Version : 1 / GB

page:

5(6)

Solubility in water

Remarks parts of solvents

pH value

Remarks inapplicable

Other information (chapter 9.)

The physical specifications are approximate values and refer to the used safety relevant component(s).

10.) Stability and reactivity

Conditions to avoid

Stable under recommended storage and handling conditions (See section 7).

Materials to avoid

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Hazardous decomposition products

When exposed to high temperatures, dangerous decomposition products such as carbon dioxide, carbon monoxide and soot can be produced.

11.) Toxicological information

Experience in practice

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause symptoms like described above by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Splashes in the eyes may cause pronounced burning pains. Prolonged contact with the eyes may lead to corneal opacity. If swallowed, stomach complaints and irritation of the digestive organs may result.

Other information (chapter 11.)

There are no data available on the preparation itself.

The product was classified in toxicological terms on the basis of the results of the calculation procedure outlined within General Directive on Preparations (88/379/EEC).

12.) Ecological information

General information / ecology

There are no data available on the preparation itself.
Do not empty into waters or drains

13.) Disposal considerations

Product

inapplicable

Uncleaned packaging

Completely emptied containers can be used in the recycling chain with glass or tinplate.
Containers with residues are to be treated as special waste.
Code of waste pursuant to European Council Directive on waste: 200122 (Municipal wastes and similar commercial, industrial and institutional wastes including separately collected fractions - aerosols).



EC safety data sheet

Trade name: SCREEN OPENER SPRAY

Status: 01.04.01

Product no.: 3514xx002

Version : 1 / GB

page:

6(6)

14.) Transport information

Land transport ADR/RID

Class	2	5	F
Hazard id. no.	23		
UN number	1950		
Technical name	Aerosols		

Marine transport IMDG/GGVSee

Class	2
Packaging group	II
UN number	1950
Proper shipping name	Aerosols
IMDG-Page:	2102
EmS	2-13
MFAG	620
MARPOL	--

Air transport ICAO/IATA

Class	2
Packaging group	II
UN number	1950
Proper shipping name	Aerosols

15.) Regulatory information

Hazard symbols

F+ Extremely flammable Xi Irritant

R phrases

37 Irritating to respiratory system.

Special labelling for certain preparations

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Do not pierce or burn, even after use

Do not spray into flames or on glowing materials.

Keep away from sources of ignition - no smoking. Keep out of reach of children. Without adequate ventilation formation of explosive mixtures may be possible.

16.) Other information

Other information

According to their chemical structure, the applied raw materials do not contain any antimony, arsenic, soluble barium, lead, cadmium, chromium, mercury and selenium.

Department issuing safety data sheet

Laboratory/product safety.

Contact person

Dipl.-Chem. G. Heller or Dipl.-Ing. U. Voetter.

The instructions are based on today's information and knowledge. The safety data sheet describes products in relation to safety requirements. These instructions do not assure application technological properties of the product.

Date of printing : 02.02.2003